



# NANOCHEM® WeldAssure™ Gas Purifiers

## Features and Benefits

- Low cost of ownership
- Wall mount frame – easy to install and operate
- Removes impurities to < 10 ppb (Dew Point = -150°F)
- **Enhances weld quality, strength and appearance**
- **Reduces weld porosity and oxidation**
- **Visual endpoint detection**
  - No guessing when to replace purifier canister
  - Color change in viewing window indicates 80% of purifier is spent
- **Increases weld electrode lifetime**
  - Do not need to stop welding to grind or replace electrode
- **Reduces weld rejects**
- **Built-in Bypass around purifier canister**
  - Enables purging of gas lines (without purifier deactivation during cylinder changeout)
- **Check valve at purifier outlet**
  - Prevents deactivation of purifier from back diffusion of atmospheric air when gas flow (and welding) is stopped
- Filters at canister inlet and outlet
- Operates at room temperature
- No power requirements
- **New NANOCHEM® In2Go™ Inorganic Media**
  - Prevents contamination from system upsets, such as air intrusion or connection of wrong gas cylinder
- **Field Replaceable Canister**
- **New Stainless Canisters can be *refilled***
  - Savings over cost of *replacement* canister
  - Reduction in generation of solid waste

NOTE: Endpoint detection not available for Ar/O<sub>2</sub> or Ar/CO<sub>2</sub> gas blends.

## Specifications

- o Flow Rates up to **100 cfh** (47 slpm / 2.8 NM<sup>3</sup>/hr)
- o Gases Purified (with **OMX™** or **In2Go™**): Argon, helium, nitrogen, hydrogen, inerts and gas blends of these constituents (4N purity or better)
- o Impurities removed (with **OMX™** or **In2Go™**): Moisture, oxygen, carbon monoxide, carbon dioxide, Nitrogen oxides, sulfur oxides, hydrogen sulfide, others  
NOTE: OMX-Plus also removes hydrocarbons  
CO is more efficiently removed by In2Go™
- o Gases Purified (with **MSA™** Media): Argon / CO<sub>2</sub>, Argon / O<sub>2</sub>, Inerts / CO<sub>2</sub> blends
- o Impurities removed with (**MSA™** media): Moisture, hydrocarbons
- o Maximum operating temperature – 65°C (170°F)
- o Maximum operating pressure – 200 psig (1.48 MPa)
- o Materials of Construction:
  - Canister (150 ml & 500 ml) – Aluminum 6061-T6
  - Canister (300 ml) – Stainless Steel, Type 304
  - Valves & Fittings – Naval Brass

## Connections

Purifier: Swagelok ¼" brass female NPT fittings  
Canister: Swagelok ¼" brass male Compression fittings



Model WA-300  
Stainless Steel canister



Model WA-500  
Aluminum canister

## Overview

The NANOCHEM® WeldAssure™ purifiers provide purge and shield gas purification for welding applications. Weld gas impurities, such as moisture and oxygen, adversely affect weld quality. These impurities are present in gas cylinders, and can also be introduced through leaks in the line or during cylinder changes. NANOCHEM® OMX™ and In2Go™ media react *chemically* and irreversibly with these impurities to deliver consistently pure gas to the weld site, improving weld quality.

NANOCHEM® OMX resin also offers efficient removal of hydrocarbons, such as compressor oils, in the gas. A new *inorganic* media, NANOCHEM® In2Go™ prevents piping system contamination in the event of a major system upset, such as significant air intrusion or from the accidental connection of an improper cylinder to the purifier.

NANOCHEM® MSA™ media is designed to purify Ar/O<sub>2</sub>, Ar/CO<sub>2</sub> and other O<sub>2</sub>, CO<sub>2</sub> blends. Only WeldAssure purifiers *specifically* labeled for oxygen or carbon dioxide applications can be used for purifying O<sub>2</sub> and CO<sub>2</sub> blends.

NANOCHEM® WeldAssure™ purifiers are an economical solution for GMAW (TIG) welding and other critical welding applications.

- Flow Rates up to 100 cfh (47 slpm)
- Available in 150 ml and 500-ml sizes – Aluminum canister  
300 ml size – Stainless steel canister
- Easy to use canister *bypass* mode for canister changes and extended shutdowns
- Reliable endpoint detection to indicate when canister is spent
- Field replaceable canisters available
- 300-ml stainless canister can be refilled, enabling savings over purchase of spare canisters

## Applications

**GTAW** (TIG), **GMAW** (MIG), **PAW** (Plasma) and **LBW** (Laser Beam) welding applications and welding overlays with GMAW and **PTAW** (Plasma Transferred Arc). Aerospace, nuclear, petrochemical, pharmaceutical, petroleum drilling, ship-building, and other manufacturing industries.

NOTE: NANOCHEM L-Series™ and MegaShield™ Purifiers with all stainless construction recommended for higher flow rates and for very clean welding in semiconductor and pharmaceutical applications. Maximum flow rates: 150 slpm (~ 300 cfh) for L-Series and 1000 slpm (~ 2000 cfh) for MegaShield Purifiers.



**MATHESON  
TRI-GAS**

ask. . . The Gas Professionals™

## Performance Benefits with NANOCHEM® Purifiers

## Overall Dimensions\*

### Welding of Aluminum 6061 T3, GTAW Process




#### Without Purification

(Impurity Content = 40 ppm)  
Surface Oxides, Porosity,  
Poor Cleaning Action,  
Poor Wetting  
Rough Weld Surface

#### With Purification

No Porosity, Clean X-Rays  
Good Cleaning Action,  
Excellent Wetting,  
Excellent Ductility  
Very Smooth Surface

### Welding of Titanium, PAW Process




#### Without Purification

Tungsten Deposits on electrode  
(<sup>3</sup>/<sub>32</sub>" EWT-2) after 30 minutes.

#### With Purification

Tungsten erosion at electrode tip  
greatly reduced

### Welding of Ferralium 255, GTAW Process




#### With Purification:

Welds bright and shiny without oxidation or heat tints. Clean Radiographs — welds free of defects. Significant improvement in weld strength (Charpy V Notch impact energy) at lower temperatures. Improvements in Mils lateral expansion and percent ductile shear fracture.

Specifications are subject to change.

MATHESON TRI-GAS and NANOCHEM are registered trademarks of Matheson Tri-Gas Inc. OMX, In2GO, HCX, and MSA, L-Series, MegaShield are trademarks of Matheson Tri-Gas Inc. Swagelok is a trademark of Swagelok Companies, Solon, Ohio, USA

Printed in USA PB R04/08



\*All dimensions in inches (mm)

NOTE: Endpoint Sight Window not available for Ar/O<sub>2</sub> and Ar/CO<sub>2</sub> purifiers

Purifier Data	Purifier Model		
	WA-150	WA-300	WA-500
Media bed volume (mL)	150	300	500
NANOCHEM Media	OMX	In2Go	OMX
NANOCHEM Media for Ar/CO <sub>2</sub> or Ar/O <sub>2</sub> blends	MSA	MSA	MSA
Canister Material	Aluminum Al6061-T6	Stainless SS 304	Aluminum Al6061-T6
Maximum Flow (cfh argon)	30	60	100
(slpm argon)	14	28	47
(NM <sup>3</sup> argon)	0.85	1.7	2.8
Dimension A / B (inches)	17 / 7	21 / 11.1	26 / 16.2
(mm)	432 / 178	533 / 282	660 / 411
Lifetime (approximate)*			
Number of cylinders purified	31	63	105

\* Based upon argon of 99.998% purity ("Pre-purified" grade) containing 3 ppm O<sub>2</sub> and 10 ppm H<sub>2</sub>O. Cylinder size – 280 ft<sup>3</sup> (7.9 NM<sup>3</sup>) – Matheson 1A, BOC 200, Air Products B, Air Liquide 44, Praxair K. NOTE: Additional impurities contributed by gas delivery system can significantly reduce predicted lifetime.

**CAUTION!** Only NANOCHEM WeldAssure purifiers specifically labeled for CO<sub>2</sub> or O<sub>2</sub> applications can be used for purifying Ar/CO<sub>2</sub> and Ar/O<sub>2</sub> blends.

DO NOT use NANOCHEM WeldAssure purifiers containing NANOCHEM OMX or In2Go media with Ar/CO<sub>2</sub> or Ar/O<sub>2</sub> blends. The Media will get very hot. OMX media will breakdown causing hydrocarbon contamination.

Ar/CO<sub>2</sub> and Ar/O<sub>2</sub> blends are often used for GMAW (MIG) welding. Benefits include a stable arc, easier arc initiation, reduced arc wandering, and reduced arc spatter. For such applications, Matheson Tri-Gas offers WeldAssure purifiers containing NANOCHEM® MSA™ media, specifically designed for CO<sub>2</sub> and O<sub>2</sub> blends.

Ar/CO<sub>2</sub> and Ar/O<sub>2</sub> blends, however, can result in deposition of oxides and carbides in the weld. Hence, for very clean GMAW welding, Matheson Tri-Gas recommends use of argon / helium blends. Use of a 75% Ar / 25% He blend and NANOCHEM OMX purification has been demonstrated to provide a very stable arc with greatly reduced weld spatter, fumes, and pyrotechnics. Weld quality of GMAW (MIG) welds with aluminum and Ferralium 255 (a duplex stainless steel) is excellent; porosity is eliminated and weld strength is as good as welds made with the GTAW (TIG) process.