


Ancillary Gas Handling and Control Equipment

Cylinder Connections

426



Description

The standard cylinder connections listed below convert cylinder valve outlets to 1/8" MPT or 1/4" MPT.

Matheson recommends dedicating equipment to a particular gas service to ensure safe and dependable operation.

Ordering Information

CGA No.	Brass 1/4" MPT (Long)	Nickel Plated Brass 1/4" MPT	Stainless Steel 1/4" MPT (Long)	Stainless Steel 1/4" MPT	Monel 1/4" MPT	Nickel Plated Brass 1/4" MPT with Check Valve	Stainless Steel 1/4" MPT with Check Valve
110	—	—	—	110-4-SS	110-4-M	—	—
170* see note below	—	—	—	—	—	—	—
180* see note below	—	—	—	—	—	—	—
240	—	—	—	240-4-SS	—	—	—
290	—	—	—	290-4-SS	—	—	—
296	296-4-B-L	296-4-BP	296-4-SS-L	—	—	—	—
320	320-4-B-L	320-4-BP	320-4-SS-L	320-4-SS	—	320-CV-4-BP	320-CV-4-SS
326	326-4-B-L	326-4-BP	326-4-SS-L	—	—	—	—
330	—	—	330-4-SS-L	330-4-SS	330-4-M	—	—
346	346-4-B-L	346-4-BP	346-4-SS-L	346-4-SS	—	346-CV-4-BP	346-CV-4-SS
350	350-4-B-L	350-4-BP	350-4-SS-L	350-4-SS	—	350-CV-4-BP	350-CV-4-SS
510	510-4-B-L	510-4-BP	510-4-SS-L	510-4-SS	—	510-CV-4-BP	510-CV-4-SS
540	540-4-B-L	540-4-BP	540-4-SS-L	540-4-SS	—	540-CV-4-BP	540-CV-4-SS
580	580-4-B-L	580-4-BP	580-4-SS-L	580-4-SS	—	580-CV-4-BP	580-CV-4-SS
590	590-4-B-L	590-4-BP	590-4-SS-L	590-4-SS	—	590-CV-4-BP	590-CV-4-SS
660	—	660-4-BP	660-4-SS-L	660-4-SS	660-4-M	—	—
670	—	—	—	—	670-4-M	—	—
677	—	—	677-4-SS-L	677-4-SS	—	—	—
678	—	—	678-4-SS-L	—	—	—	—
679	—	—	—	—	679-4-M	—	—
680	—	—	680-4-SS-L	—	—	—	—
695	—	—	695-4-SS-L	695-4-SS	—	—	—
703	—	—	703-4-SS-L	—	—	—	—
705	—	—	705-4-SS-L	705-4-SS	—	—	—

Shipping Weight: 1 lb

* 1/8" MPT:

- 170-2-BP Nickel Plated Brass
- 170-2-SS Stainless Steel
- 180-2-BP Nickel Plated Brass
- 180-2-SS Stainless Steel
- 180-2-M Monel

Ancillary Equipment