



348 Hardware Mechanical Specifications

(Note that Matheson Tri-Gas reserves the right to change specifications without notice.)

| Model | L-Series | L-Series High Flow | H-Series | HP-Series |
|--|--|---|---|------------------|
| Model Numbers | L-60 L-300 L-500 L-2000 | L-300-HF L-500-HF L-2000-HF | H-500 | HP-300 HP-500 |
| Media Bed Volume | 60 mL 300 mL 500 mL 2000 mL | 300 mL 500 mL 2000 mL | 500 mL | 300 mL 500 mL |
| Connection Type | 1/4" face seal (female inlet, male outlet) | | | |
| Valve Type | 1/4" springless diaphragm valve | | 1/4" springless diaphragm or bellows valve | |
| Valve Actuation | Manual | | Manual or Pneumatic | |
| Wetted Part Materials | 316L Stainless Steel Nickel 200 gaskets Elgiloy diaphragm PCTFE valve seat | | 316L Stainless Steel Nickel 200 gaskets 300 Series Stainless Steel bellows, or Elgiloy diaphragm PCTFE valve seat or insert | |
| Outlet Filter Material | 316L Stainless Steel or PTFE | | | |
| Outlet Filter Performance | 99.9999999% (9-log) of all particles ≥ 0.003 μm, except L-500-HF which is 99.99% (4-log) of all particles ≥ 0.003 μm ⁽⁵⁾ | | | |
| Inboard Leak Rate | 1 x 10 ⁻⁹ sccs of helium | | | |
| Maximum Pressure (psig) | L-60 L-300 L-500 L-2000 | 500 500 ⁽¹⁾ 500 ⁽¹⁾ 500 ⁽¹⁾ | 500 ⁽¹⁾ | 2,850 |
| Temperature Range | -40°C to 70°C | | | |
| Maximum Typical Flow⁽²⁾ (slpm of nitrogen) | L-60 L-300 L-500 L-2000 | 8 15 50 50 | L-300-HF 50 L-500-HF 75 L-2000-HF 150 | 50 50 50 |
| Bypass | 3-Valve Bypass, Optional and Retrofittable | | Standard | |
| Endpoint Detection | Available for NANOCHEM® OMX, OMX Plus, OMA and OMS media only (except L-60) | | | N/A |
| Exhausted Enclosure | Please contact Matheson Tri-Gas Equipment Customer Service Center at (800) 828-4313 | | | |

- Note 1: The endpoint detector, if fitted, limits the maximum pressure rating to 150 psig.
- Note 2: The maximum typical flow is dependent both on the allowable pressure drop through the filter element, and the characteristics of the purification media. Higher flows may be possible. Contact Matheson Tri-Gas Equipment Customer Service Center at (800) 828-4313, for recommendations for specific applications and/or refer to the pressure drop curves for that purifier model.
- Note 3: All MS-4, MS-8, MS-16 and MS-32 purifiers for ammonia service come with a filter which removes 99.9999999% (9-log) of all particles ≥ 0.003mm. This filter limits the maximum flow to 150 slpm of nitrogen.
- Note 4: Valves on all MS-Series purifiers have 1/2" VCR type inlet and outlet connections, but are connected to 3/8" Stainless Steel tubing.
- Note 5: Filters on all L-Series purifiers provide 9-log retention at the highest rated flow rate for particles ≥ 0.003μm. The exception is the filter on the L-500-HF. While it offers 9-log retention at low flow rates (up to 6 lpm), the removal efficiency decreases to 4-log retention at the maximum rated flow rate of 75 slpm.



Hardware Mechanical Specifications *(continued)*

(Note that Matheson Tri-Gas reserves the right to change specifications without notice.)

| Model | MegaShield | A-Series | White Knight | |
|--|--|---|--|---|
| Model Numbers | MS-4 MS-8 MS-16 MS-32 | A-60 A-300 A-500 A-2000 | WK-75 WK-500 WK-2500 | WK-9000 |
| Media Bed Volume | 4 liters 8 liters 16 liters 32 liters | 60 mL 300 mL 500 mL 2000 mL | 55 mL 500 mL 2500 mL | 9000 mL |
| Connection Type | 1/2" face seal (female) ⁽⁴⁾ | 1/4" face seal (female inlet, male outlet) | 1/4" male face seal (inlet and outlet) | 1/2" face seal (female inlet, male outlet) |
| Valve Type | 3/8" springless diaphragm valve ⁽⁴⁾ | 1/4" springless diaphragm valve | Poppet valve | 3/8" springless diaphragm valve |
| Valve Actuation | Manual | Manual | Manual during installation | Manual |
| Wetted Part Materials | 316L Stainless Steel Nickel 200 gaskets PCTFE valve seat TFE comp. ring | 316L Stainless Steel Nickel 200 gaskets Elgiloy diaphragm PCTFE valve seat | 316L Stainless Steel Nickel 200 gaskets | 316L Stainless Steel Nickel 200 gaskets Elgiloy diaphragm PCTFE comp. ring |
| Outlet Filter Material | 316L Stainless Steel | 316L Stainless Steel or PTFE | 316L Stainless Steel | PTFE |
| Outlet Filter Performance | 100 µm | 99.999999% (9-log) of all particles ≥ 0.003 µm | | |
| Inboard Leak Rate | 1 x 10 ⁻⁹ sccs of helium | | | |
| Maximum Pressure (psig) | 350 | 500 | WK-75 3000 WK-500 500 WK-2500 150 | 150 |
| Temperature Range | -40°C to 70°C | | | |
| Maximum Typical Flow⁽²⁾ (slpm of nitrogen) | 1000 | A-60 8 A-300 15 A-500 50 A-2000 150 | WK-75 5 WK-500 60 WK-2500 300 | 1000 |
| Bypass | 3-Valve Bypass, Optional and Retrofittable | N/A | | |
| Endpoint Detection | Available for NANOCHEM® OMX, OMA and OMS media only | Available for NANOCHEM® OMX, OMX-Plus, OMA and OMS media only (except A-60) | N/A | |
| Exhausted Enclosure | Special Order | SideCar | N/A | |

- Note 1: The endpoint detector, if fitted, limits the maximum pressure rating to 150 psig.
- Note 2: The maximum typical flow is dependent both on the allowable pressure drop through the filter element, and the characteristics of the purification media. Higher flows may be possible. Contact Matheson Tri-Gas Equipment Customer Service Center at (800) 828-4313, for recommendations for specific applications and/or refer to the pressure drop curves for that purifier model.
- Note 3: All MS-4, MS-8, MS-16 and MS-32 purifiers for ammonia service come with a filter which removes 99.999999% (9-log) of all particles ≥ 0.003mm. This filter limits the maximum flow to 150 slpm of nitrogen.
- Note 4: Valves on all MS-Series purifiers have 1/2"- VCR type inlet and outlet connections, but are connected to 3/8" Stainless Steel tubing.
- Note 5: Filters on all L-Series purifiers provide 9-log retention at the highest rated flow rate for particles ≥ 0.003µm. The exception is the filter on the L-500-HF. While it offers 9-log retention at low flow rates (up to 6 lpm), the removal efficiency decreases to 4-log retention at the maximum rated flow rate of 75 slpm.